

SAFETY DATA SHEET

TORK PREMIUM ANTIMICROBIAL FOAM CLEANSER

Infosafe No.: LQ0NP
ISSUED Date: 06/02/2017
Issued by: ASALEO CARE

1. IDENTIFICATION

GHS Product Identifier

TORK PREMIUM ANTIMICROBIAL FOAM CLEANSER

Company Name

ASALEO CARE

Address

30 - 32 Westall Road Springvale
Vic 3171 Australia

Telephone/Fax Number

Tel: +61 3 9550 2999
Fax: +61 3 9547 8165

Emergency phone number

+61 3 9550 2999 (BH)

Recommended use of the chemical and restrictions on use

Skin disinfectant

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Eye Damage/Irritation: Category 2A

Flammable Liquids: Category 3

Signal Word (s)

WARNING

Hazard Statement (s)

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

Pictogram (s)

Flame, Exclamation mark



Precautionary statement – Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P264 Wash contaminated skin thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use carbon dioxide, dry chemical or foam for extinction.

Precautionary statement – Storage

P403+P235 Store in a well-ventilated place. Keep cool.

Precautionary statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Name	CAS	Proportion
Ethanol	64-17-5	30-40 %
Isopropyl alcohol	67-63-0	<5 %
Other ingredients determined not to be hazardous	Not required	Balance

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

Ingestion

Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.

Skin

Wash affected area thoroughly with soap and water. If symptoms develop seek medical attention.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use carbon dioxide, dry chemical or foam.

Unsuitable Extinguishing Media

Do not use water jet.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific Hazards Arising From The Chemical

Flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code

•2Y

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with local exhaust ventilation, away from sparks, flames and other ignition sources. Use approved flammable liquid storage containers in the work area. Prevent release of vapours and mists into workplace air. Keep containers tightly closed. Take precautionary measures against static discharges. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

Storage Temperatures

>0-30°C

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure value assigned for this material. However, the available exposure limits for ingredients are listed below:

Ethanol

TWA: 1000 ppm, 1880 mg/m³

Isopropyl alcohol

TWA: 400 ppm, 983 mg/m³

STEL: 500 ppm, 1230 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-

hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Biological Limit Values

Name: 2-Propanol (CAS 67-63-0)

Determinant: Acetone in urine

Value: 40 mg/L

Sampling time: End of shift at end of workweek

Notation: B, Ns

Source: American Conference of Industrial Hygienists (ACGIH)

Appropriate Engineering Controls

Industrial applications: This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1:2009 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

Respiratory Protection

Not normally required under normal conditions of use. Use only with adequate ventilation. Avoid breathing of vapours, mists or spray.

Industrial applications: If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Not normally required under normal conditions of use.

Industrial applications: Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Not normally required under normal conditions of use.

Industrial applications: Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Description	Properties	Description
Form	Liquid	Appearance	Liquid
Colour	Colourless	Odour	Alcohol
Decomposition Temperature	Not available	Melting Point	Not available
Boiling Point	Not available	Solubility in Water	Extremely soluble (40-99%)
pH	Not available	Vapour Pressure	Not available
Vapour Density (Air=1)	Not available	Evaporation Rate	Not available
Odour Threshold	Not available	Viscosity	1-50cP
Partition Coefficient: n-octanol/water	Not available	Density	0.935 kg/l
Flash Point	28°C	Flammability	Flammable liquid
Auto-Ignition Temperature	Not available	Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available		

10. STABILITY AND REACTIVITY

Reactivity

Reacts with incompatible materials.

Chemical Stability

Stable under normal conditions of storage and handling.

Conditions to Avoid

Heat, open flames and other sources of ignition.

Incompatible materials

Strong oxidising agents.

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases including: carbon dioxide and carbon monoxide.

Possibility of hazardous reactions

Not available

11. TOXICOLOGICAL INFORMATION

Toxicology Information

Toxicity data for ingredients is given below.

Acute Toxicity - Oral

Ethanol

LD50 (rat): 6200 mg/kg (24h)

Isopropyl alcohol

LD50 (rat): 5045 mg/kg (24h)

Acute Toxicity - Inhalation

Ethanol

LC50 (rat): 124.7 ppm/4h

Isopropyl alcohol

LC50 (rat): 72.6 mg/4h

LC50 (rat): 64,000 ppm/4h (V)

LC50 (rat): 16,000 ppm/8h (V)

Acute Toxicity - Dermal

Ethanol

LD50 (rat): >20,000 mg/kg (24h)

Isopropyl alcohol

LD50 (rat): 15,8000 mg/kg (24h)

Ingestion

Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

Inhalation

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system. May casue headaches and dizziness.

Skin

May be irritating to skin. The symptoms may include redness, itching and swelling.

Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ cell mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Not considered to be a carcinogenic hazard.

Isopropyl alcohol is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

Reproductive Toxicity

Not considered to be toxic to reproduction.

STOT-single exposure

Not expected to cause toxicity to a specific target organ.

STOT-repeated exposure

Not expected to cause toxicity to a specific target organ.

Aspiration Hazard

Not expected to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The available ecological data is given below.

Persistence and degradability

Not available

Mobility

Miscible with water

Bioaccumulative Potential

Not available

Other Adverse Effects

Not available

Environmental Protection

Do not discharge this material into waterways, drains and sewers.

Acute Toxicity - Fish

Ethanol

LC50 (Rainbow trout, *Oncorhynchus mykiss*): 13,480 mg/l/96h

LC50 (fathead minnow, *Pimephales promelas*): 13,480 mg//96h

Isopropyl alcohol

LC50 (fathead minnow, *Pimephales promelas*): 9,640 mg/l/96h

LC50 : 1000 mg/l/96h

Acute Toxicity - Daphnia

Ethanol

LC50 (Freshwater water flea, Daphnia magna): 5400 mg/l/48h

EC50 (Freshwater water flea, Daphnia magna): 10,800 mg/l/24h

Isopropyl alcohol

LC50 (Freshwater water flea, Daphnia magna): 2285 mg/l/48h

EC50 (Freshwater water flea, Daphnia magna): 13,299 mg/l/48h

EC50 (Freshwater water flea, Daphnia magna): 10 - 100 mg/l/24h

Acute Toxicity - Algae

Ethanol

IC50: 0.02 mg/l/72h

Isopropyl alcohol

EC50 : 1 - 10 mg/l/24h

13. DISPOSAL CONSIDERATIONS

Disposal considerations

Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld on or near containers. Empty containers may contain flammable residues. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Advise flammable nature.

14. TRANSPORT INFORMATION

Transport Information

This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:

- Class 1: Explosives

- Division 2.1: Flammable Gases.

(Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L)

- Division 2.3: Toxic Gases

- Division 4.2: Spontaneously Combustible Substances

- Division 5.1: Oxidising substances

- Division 5.2: Organic Peroxides

- Class 6: Toxic or Infectious Substances

(where the flammable liquid is nitromethane)

- Class 7: Radioactive materials unless specifically exempted.

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Class/Division: 3

UN No: 1170

Proper Shipping Name: ETHANOL SOLUTION

Packing Group: III

EMS: F-E, S-D

Special Provisions: 144, 223

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Class/Division: 3

UN No: 1170

Proper Shipping Name: Ethanol solution

Packing Group: III
Packaging Instructions (passenger & cargo): 355
Packaging Instructions (cargo only): 366
Hazard Label: Flammable Liquid
Special Provisions: A3, A58, A180

U.N. Number

1170

UN proper shipping name

ETHANOL SOLUTION

Transport hazard class(es)

3

Packing Group

III

Hazchem Code

•2Y

Special Precautions for User

Not available

IERG Number

14

IMDG Marine pollutant

No

Transport in Bulk

Not available

15. REGULATORY INFORMATION

Regulatory information

Classified as Hazardous according to the Globally Harmonised System of classification and labelling of chemicals (GHS) including Work, Health and Safety regulations, Australia

Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Poisons Schedule

Not Scheduled

16. OTHER INFORMATION

Date of preparation or last revision of SDS

SDS reviewed: February 2017

Supersedes: November 2011

References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of classification and labelling of chemicals.

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.